


Distributor block TX

Technical details

Temperature range	0°C ... +60°C
Input range	2.5 ... 16 bar
Mounting	arbitrary
Medium	compressed air according to ISO 8573-1:2010, neutral gases
Materials	Body: zinc diecasting, seals: NBR, inner parts: plastic and brass



Distributor block, 4 outlets

Order code

Series		TX-***-00-0-000*		Versions	
Connection / Size		Digit 4	Width		
14	G1/4 / X1	1	standard		
37	G3/8 / X1	3	small (only for G1/4 and G1/2)		
12	G1/2 / X2				
34	G3/4 / X2				

Technical data

Model-no.:	TX-14-00-0-0001	TX-14-00-0-0003	TX-37-00-0-0001	TX-12-00-0-0001	TX-12-00-0-0003	TX-34-00-0-0001
Connection	G1/4	G1/4	G3/8	G1/2	G1/2	G3/4
Size	X1	X1	X1	X2	X2	X2
Connection 2.1 (bottom)	G1/4	G1/4	G1/4	G1/2	G3/8	G1/2
Connection 2.2 (top)	G1/4	G1/4	G1/4	G1/2	G1/8	G1/2
Connection 2.3 (front)	G1/4	G1/4	G1/4	G1/4	G1/4	G1/4
Connection 2.4 (rear)	G1/4	G1/4	G1/4	G1/4	G1/4	G1/4
Flow (1-2 in NI/min)	2500	3300	2500	11000	11000	11000
Flow (1-2.1 in NI/min)	2000	2300	2000	8750	3450	8750
Flow (1-2.2 in NI/min)	2000	1100	2000	8750	1400	8750
Flow (1-2.3 in NI/min)	900	2300	900	1300	3100	1300
Flow (1-2.4 in NI/min)	900	2300	900	1300	3100	1300
Weight (kg)	0.32	0.19	0.28	0.66	0.36	0.66