



Technical details


Temperature range	0°C ... +50°C
Input range	max. 16 bar (size Y0 max. 12 bar)
Mounting	arbitrary
Medium	compressed air according to ISO 8573-1:2010, neutral gases
Materials	Body: Grivory (PA66), seals: NBR, inner parts: plastic and brass



Distributor block, 2 outlets
Series KY-04, KY-34, KY-10



Distributor block, 3 outlets
Series KY-14, KY-37



Distributor block, 4 outlets
Series KY-38, KY-12

Order code

Series	TY-**-00-0-0001
Connection / Size	
04	G1/4 / Y0
14	G1/4 / Y1
37	G3/8 / Y1
38	G3/8 / Y2
12	G1/2 / Y2
34	G3/4 / Y3
10	G1 / Y3

Distributor block TY

Technical data

Model-no.:	TY-04-...	TY-14-...	TY-37-...	TY-38-...	TY-12-...	TY-34-...	TY-10-...
Connection	G1/4	G1/4	G3/8	G3/8	G1/2	G3/4	G1
Size	Y0	Y1	Y1	Y2	Y2	Y3	Y3
Connection 2.1 (bottom)	G1/4	G1/4	G1/4	G3/8	G3/8	G3/4	G3/4
Connection 2.2 (top)	G1/4	G1/4	G1/4	G1/4	G1/4	G3/4	G3/4
Connection 2.3 (front)	-	G1/4	G1/4	G3/8	G3/8	-	-
Connection 2.4 (backward)	-	-	-	G3/8	G3/8	-	-
Flow (1-2 in NI/min)	2300	2700	2700	7250	7250	18000	18000
Flow (1-2.1 in NI/min)	950	2000	2000	5500	5500	12000	12000
Flow (1-2.2 in NI/min)	2000	2000	2000	22500	22500	8500	8500
Flow (1-2.3 in NI/min)	-	900	900	2300	2300	-	-
Flow (1-2.4 in NI/min)	-	-	-	2300	2300	-	-
Weight (kg)	0.10	0.19	0.17	0.35	0.33	0.88	0.82

Accessories


Coupling kits for wall mounting KPY-W



Coupling kits KPY-K



Mounting brackets WYP



Details: see page 12-23