

## Form B industrial norm

<b>Overall width</b>	22 mm
<b>Contact distance</b>	11 mm
<b>Contacts</b>	2P + E
<b>Protection</b>	IP 65 according to EN 60529 with connected plug socket
<b>Duty cycle</b>	100 %
<b>Temperature range*</b>	-20°C...+50°C
<b>Voltage tolerance</b>	± 10 %
<b>For use with series</b>	86-MV-5-28, 86-MV-5-14, 86-MV-5-24, 86-MV-5-38, 86-MV-5-12, 86-MV-3, 86-MN-4

\* The max. applicable operating temperature depends on the temperature specification of the used valve.



<b>Model-no.:</b>	86-SP-011-412	86-SP-011-427
<b>Voltage</b>	24 V DC	220 V AC
<b>Power consumption DC</b>	3 W	-
<b>Power consumption AC</b>	-	3.5 VA

## Form C industrial norm

<b>Overall width</b>	15 mm
<b>Contact distance</b>	9.4 mm
<b>Contacts</b>	2P + E
<b>Protection</b>	IP 65 according to EN 60529 with connected plug socket
<b>Duty cycle</b>	100 %
<b>Temperature range*</b>	-20°C...+50°C
<b>Voltage tolerance</b>	± 10 %
<b>For use with series</b>	86-MV-5-18

\* The max. applicable operating temperature depends on the temperature specification of the used valve.



<b>Model-no.:</b>	86-SP-021-412	86-SP-021-427
<b>Voltage</b>	24 V DC	220 V AC
<b>Power consumption DC</b>	2.5 W	-
<b>Power consumption AC</b>	-	2.5 VA