


Technical details

Temperature range	0°C ... +50°C
Input range	max. 16 bar (size Y0 max. 12 bar)
Mounting	arbitrary
Medium	compressed air according to ISO 8573-1:2010, neutral gases
Materials	Body: Grivory (PA66), seals: NBR, inner parts: plastic and brass



3/2 directional control valve, operated by a knob, 3-fold.
 Locking: rotary lock and padlock possible.
 Silencer is mounted in exhaust.


Order code

		KY-**-00-0-0001
Series		←
Connection / Size		←
04	G1/4 / Y0	
14	G1/4 / Y1	
37	G3/8 / Y1	
38	G3/8 / Y2	
12	G1/2 / Y2	
34	G3/4 / Y3	
10	G1 / Y3	

Technical data

Model-no.:	KY-04-...	KY-14-...	KY-37-...	KY-38-...	KY-12-...	KY-34-...	KY-10-...
Connection	G1/4	G1/4	G3/8	G3/8	G1/2	G3/4	G1
Size	Y0	Y1	Y1	Y2	Y2	Y3	Y3
Flow (1-2 in NI/min)	2300	1900	1900	11000	11000	25000	25000
Weight (kg)	0.10	0.27	0.26	0.54	0.52	1.19	1.15