

## Non-return valve NY

### Technical details

<b>Temperature range</b>	0°C ... +50°C
<b>Input range</b>	2.5 ... 16 bar ( size Y0 max. 12 bar )
<b>Mounting</b>	arbitrary
<b>Medium</b>	compressed air according to ISO 8573-1:2010, neutral gases
<b>Materials</b>	Body: Grivory (PA66), seals: NBR, inner parts: plastic, stainless steel and brass



Poppet valve, spring loaded.



### Order code

		<b>NY-**-00-0-0001</b>
Series		←
Connection / Size		←
04	G1/4 / Y0	
14	G1/4 / Y1	
37	G3/8 / Y1	
38	G3/8 / Y2	
12	G1/2 / Y2	
34	G3/4 / Y3	
10	G1 / Y3	

### Technical data

Model-no.:	NY-04-...	NY-14-...	NY-37-...	NY-38-...	NY-12-...	NY-34-...	NY-10-...
<b>Connection</b>	G1/4	G1/4	G3/8	G3/8	G1/2	G3/4	G1
<b>Size</b>	Y0	Y1	Y1	Y2	Y2	Y3	Y3
<b>Flow (l/min)</b>	2000	2000	2000	4500	4500	10000	10000
<b>Weight (kg)</b>	0.14	0.24	0.22	0.54	0.52	0.79	0.63